- \bigcirc Quantity includes provision for laps required in longitudinal reinforcing as follows: 65' thru 100' Spans - 1 lap
- \bigcirc Quantity includes provision for laps required in longitudinal reinforcing as follows:
 65' Span
 70' thru 100' Spans - 1 1/2 laps
 Laps account for adjacent span combinations and are approximate. Pay quantity will be as shown on the plans.
- (J) At abutments, provide and install Fixed Bearing Assemblies of the size, shape and location as detailed in the plans. See schedule for estimated total of structural steel per span for the Fixed Bearing Assemblies. Include all costs associated with providing and installing the Anchor Plate and Anchor Bars, including all material, labor, equipment and incidentals necessary to complete the work shown in the plans in the contract unit price of FIXED BEARING ASSEMBLIES.
- 4 At all piers, provide and install Expansion Bearing Assemblies of the size, shape and location as detailed in the plans. See schedule for estimated total of structural steel per span for the Expansion Bearing Assemblies. Include all costs associated with providing and installing the Elastomeric Pads, Anchor Plates, Contact Plates, Anchor Bars and Anchor Bolts, Nuts and Washers, including all material, labor, equipment and incidentals necessary to complete the work shown in the plans in the contract unit price of EXPANSION BEARING ASSEMBLIES.

SUPERSTRUCTURE QUANTITIES PER SPAN

ABUTMENT TO PIER

(J) the top surface of the Beams and the bottom surface of the Deck Slab. The Elastomeric Pads are to be of the size and shape as detailed in the plans and located at each Beam end above the Piers. Include all costs associated with providing and installing the Elastomeric Pads above the Beams, including all material, labor, equipment, and incidentals necessary to complete the work as shown in the plans, in the contract unit price of ELASTOMERIC BEARING PADS.

339 359 379	339	339	0		75' 299 1	70' 279 1	65' 259 1		(L.F.)	PRESTRESSED CONCRETE BEAMS			
191.0	87.0)	171.0	161.0	151.0	141.0	131.0		(L.F.)	CONCRETE RAIL (TR4)		S	
-	150	150	150	150	150	150	150		(LB.)	STRUCTURAL STEEL		SUPERSTRUCTURE QUANTITIES PER SPAN	
-	152.9	147.3	141.7	136.0	130.4	124.8	119.1		(C.Y.)	CLASS AA CONCRETE	ABUTMENT	TURE QUA	
	26 44N	25,330	24,090	22,980	21,750	20,630	19,400	TR4 W/ OPENINGS	(LB.)	EPOXY COATED REINFORCING STEEL	ABUTMENT TO ABUTMENT	INTITIES P	
1	27,340	26,110	24,890	23,660	22,440	21,210	19,990	TR4 W/O OPENINGS]. <u></u>	COATED RCING EL	NT	ER SPAN	
	378	360	342	324	307	289	272	TR4 W/ OPENINGS	(S.	WATER REPELLENT (VISUALLY INSPECTED)			
	371	354	337	319	302	285	267	TR4 W/O OPENINGS	(S.Y.)	EPELLENT INSPECTED)			
	8	8	8	8	8	8	8	(3)	(EACH)	(PL) FIXED BEARING			

90'	85'	80'	75'	70'	65'		SPAN				100'	95'	90'	85'	80'	75'	70'	65'			0 0 0 N	
359	339	319	299	279	259		(L.F.)	PRESTRESSED CONCRETE BEAMS			399	379	359	339	319	299	279	259		(L.F.)	PRESTRESSED CONCRETE BEAMS (TYPE TV)	
180.0	170.0	160.0	150.0	140.0	130.0		(L.F.)	CONCRETE RAIL (TR4)			200.5	190.5	180.5	170.5	160.5	150.5	140.5	130.5		(L.F.)	CONCRETE RAIL (TR4)	
450	450	450	450	450	450		(LB.)	STRUCTURAL STEEL		SUPE	300	300	300	300	300	300	300	008		(LB.)	STRUCTURAL STEEL	
106.9	101.3	95.7	90.0	84.4	78.8		(C.Y.)	CLASS AA CONCRETE		SUPERSTRUCTURE	138.4	132.8	127.1	121.5	115.9	110.2	104.6	99.0		(C.Y.)	CLASS AA CONCRETE	
25,040	23,930	22,700	21,580	20,350	19,150	TR4 W/ OPENINGS	(LB.)	EPOXY COATED REINFORCING STEEL	PIER TO	RE QUANTITIES	27,620	26,390	25,280	24,040	22,930	21,700	20,580	19,270	TR4 W/ OPENINGS	(LB.)	EPOXY COATED REINFORCING STEEL	
25,720	24,500	23,270	22,050	20,820	19,520	TR4 W/O OPENINGS	8.)	COATED ORCING	PIER	ITIES PER	28,400	27,170	25,950	24,720	23,500	22,270	21,050	19,750	TR4 W/O OPENINGS	3.) (c	COATED ORCING	
317	300	282	265	247	229	TR4 W/ OPENINGS	(S.	WATER RI		SPAN	374	357	339	321	303	286	268	251	TR4 W/ OPENINGS	(S.	WATER RI (VISUALLY	
312	294	277	260	242	225	TR4 W/O OPENINGS	(S.Y.)	WATER REPELLENT (VISUALLY INSPECTED)			367	350	333	315	298	281	264	246	TR4 W/O OPENINGS	(S.Y.)	WATER REPELLENT (VISUALLY INSPECTED)	
8	8	8	8	8	8	4)	ASSEMBLY (EACH)	(PL) EXPANSION BEARING			4	4	4	4	4	4	4	4	(3)	(EACH)	(PL) FIXED BEARING	
8	8	8	8	8	8	(5)	(EACH)	(PL) ELASTOMERIC BEARING			4	4	4	4	4	4	4	4	4	(EACH)	(PL) EXPANSION BEARING	
								<u> </u>			4	4	4	4	4	4	4	4	5	(EACH)	(PL) ELASTOMERIC BEARING BAARS	

İ		
GAL.		(SP) SEALER RESIN
L.F.		(SP) SEALER CRACK PREPARATION
TINU		ITEM
NAU	\sim	CONSTRUCTION JOINT SEAL QUANTITIES

100' 95 90' 85 80' 75 70' 65

350 350 350 350 350 350

720

1,440 1,420 1,400

700 700 700 700 700 700

700 700

> 710 700 690 680

SPAN

ABUTMENT TO ABUTMENT

ABUTMENT TO PIER

PIER TO PIER

BEARING ASSEMBLY STRUCTURAL STEEL QUANTITIES PER SPAN

FIXED
BEARING
(LB.)

FIXED EXPANSION
BEARING BEARING
ASSEMBLIES ASSEMBLIES
(LB.) (LB.)

EXPANSION
BEARING
ASSEMBLIES
(LB.)

350 350

660

670 670

1,340

1,340 1,320

100' 95

399 379

200.0 190.0

450 450

118.2 112.6

27,390 26,280

28,170 26,950

353 336

346 329

 ∞ ω

 ∞ ω

1,380 1,360

10-10-05

OKLAHOMA DEPT. OF TRANSPORTATION
BRIDGE STANDARD (ENGLISH)
SUPERSTRUCTURE QUANTITIES
TYPE IX P.C. BEAMS
INTEGRAL