




PLAN




ELEVATION



TYPICAL SECTION THRU ABUTMENT



SIDE VIEW



DETAILS OF BENT REINFORCING STEEL

BAR LIST - ONE ABUTMENT					
MARK	NO.	SIZE	FORM	LENGTH	LENGTH VARIATION
BH1	10	#4	STR.	28'-8"	-
BH2	8	#4	BNT.	30'-4"	-
BH3	10	#9	STR.	28'-8"	-
BH4	21	#4	BNT.	5'-7"	-
BV1	30	#4	STR.	9'-2" AVG.	9'-0" TO 9'-4"
BV2	30	#5	STR.	9'-2" AVG.	9'-0" TO 9'-4"
P1	18	#4	BNT.	6'-6"	-
P2	12	#4	BNT.	8'-0"	-
S1	30	#5	BNT.	14'-1"	-
SC	6	#4	BNT.	4'-0"	-
WT1	2	#6	BNT.	9'-2"	-
WT2	4	#6	BNT.	7'-2" AVG.	5'-10" TO 8'-6"
WT3	8	#6	BNT.	18'-0"	-
WT4	14	#6	BNT.	11'-0"	-

③ NO. INCLUDES TWO SETS OF 15 BARS
 ④ NO. INCLUDES TWO SETS OF 2 BARS

SUMMARY OF QUANTITIES - ONE ABUTMENT ⑤		
ITEM	UNIT	TOTAL
SUBSTRUCTURE EXCAVATION, COMMON	CY	65.00
GRANULAR BACKFILL	CY	44.00
CLASS A CONCRETE	CY	23.30
REINFORCING STEEL	LB	3,000.00
PILES, FURNISHED (HP 12X53)	LF	-
PILES, DRIVEN (HP 12X53)	LF	-
6" PERFORATED PIPE UNDERDRAIN	LF	26.00
6" NON-PERFORATED PIPE UNDERDRAIN	LF	-

⑤ EXCLUDES WINGS

① DIMENSIONS ARE FROM TOP OF BRIDGE SEAT AT FRONT FACE OF BACKWALL.
 ② ALL WT WING REINFORCING STEEL TIED TO THE ABUTMENT BRIDGE SEAT, BACKWALL AND CURTAIN WALL REINFORCING STEEL MUST BE IN PLACE PRIOR TO POURING ABUTMENT CONCRETE. FOR ADDITIONAL INFORMATION SEE WING DETAILS.

APPROVED BY BRIDGE ENGINEER *Robert J. Dush* DATE 10-31-2011
 OKLAHOMA DEPARTMENT OF TRANSPORTATION
 COUNTY BRIDGE STANDARD (ENGLISH)
ABUTMENT DETAILS
TYPE IV P.C. BEAMS
 26' CLEAR ROADWAY - CONVENTIONAL - SKEWED 0°
 2009 SPECIFICATIONS CB26-C-SKO-ABUT-PC4 02E
 CB-152E