




PLAN




ELEVATION



SECTION A-A



TYPICAL SECTION THRU SEAT



PILE SCHEDULE						
SPAN	TOTAL NUMBER OF PILES	N	A	B	C	MAXIMUM FACTORED PILE LOAD
95'	10	4	4'-6"	2'-3"	2'-3"	78.1 TON
100'	11	5	4'-0"	0"	2'-6"	72.9 TON
105'	11	5	4'-0"	0"	2'-6"	74.9 TON
110'	11	5	4'-0"	0"	2'-6"	76.8 TON
115'	12	5	3'-8"	1'-10"	2'-4"	72.2 TON
120'	12	5	3'-8"	1'-10"	2'-4"	74.0 TON
125'	12	5	3'-8"	1'-10"	2'-4"	75.8 TON
130'	12	5	3'-8"	1'-10"	2'-4"	77.5 TON

Place all WT Wing reinforcing tied to Abutment Seat reinforcing before placing Abutment Seat concrete. Do not place Abutment Wing concrete until concrete for the Abutment Diaphragm and Deck Slab have attained a strength of 3000 p.s.i. For additional details, see ABUTMENT DIAPHRAGM DETAILS (SHEET 1 OF 2 AND SHEET 2 OF 2) and ABUTMENT WING DETAILS (SHEET 2 OF 2).

ABUTMENT SEAT BAR LIST						
MARK	SIZE	NO.	FORM	LENGTH	LENGTH VARIATION	
EPOXY COATED REINFORCING						
BV1	#7	154	STR.	6'-7"		
BH1	#8	8	STR.	44'-8"		
BH2	#4	12	STR.	44'-8"		
BS1	#4	46	BNT.	12'-9"		
P1	#4	24	BNT.	5'-5"		
P2	#4	16	BNT.	7'-8"		
WT1	#4	2	BNT.	5'-2"		
WT2	#8	2	BNT.	11'-2"		
WT3	#4	10	STR.	7'-2" AVG.	4'-2" to 10'-2"	
WT4	#8	10	BNT.	8'-6" AVG.	5'-6" to 11'-6"	
10 PILE ABUTMENT						
BH3	#4	30	BNT.	3'-7"		
11 PILE ABUTMENT						
BH3	#4	33	BNT.	3'-7"		
12 PILE ABUTMENT						
BH3	#4	36	BNT.	3'-7"		

① 2 Sets of 5

APPROVED BY BRIDGE ENGINEER *Scott J. Luch* DATE *4/2/10*

OKLAHOMA DEPT. OF TRANSPORTATION
BRIDGE STANDARD (ENGLISH)
ABUTMENT DETAILS
TYPE BT-72 AND TYPE J P.C. BEAMS
INTEGRAL (SHEET 1 OF 2)

2009 SPECIFICATIONS | B40-I-ABUT-PC5-1 | 01E
B-46E