


S	ECTION	N TH	IRU	WING	A	<u>T</u>
BACK	FACE	OF	AB	UTMEN	IT	SEAT


	0		Α	BUTME	NT BAR LIS	T
- [MARK	SIZE	NO.	FORM	LENGTH	LENGTH VARIATION
			EPC	XY COA	TED REINFORC	CING
	BH1	#4	9	STR.	44'-0"	
	BH2	#4	7	BNT.	45'-4"	
	внз	#9	10	STR.	44'-0"	
	BH4	#4	21	BNT.	5'-1"	
D	BV1	#4	42	STR.	7'-10" Avg.	7'-7" to 8'-1"
D	BV2	#5	42	STR.	7'-10" Avg.	7'-7" to 8'-1"
	вуз	#4	8	STR.	8'-8"	
	S 1	#5	45	BNT.	12'-11"	
	SC	#4	4	BNT.	3'-3"	
	WT1	#5	2	BNT.	8'-2"	
2)	WT2	#5	6	BNT.	8'-8" Avg.	5'-8" to 11'-8"
	WT3	#5	10	BNT.	16'-8"	
	WT4	#5	20	BNT.	10'-8"	
	WH1	#5	36	STR.	16'-8"	
3)	WH2	#5	24	STR.	9'-6" Avg.	5'-9" to 13'-3"
ı	WH3	#5	4	BNT.	17'-5"	
ı	WV1	#4	16	STR.	4'-0"	
a)	WV2	#4	56	STR.	6'-5" Avg.	4'-4" to 8'-6"
	WP1	#4	6	BNT.	8'-8"	
	WP2	#4	8	STR.	1'-7"	



ABU	ITMEN	T BA	R LIST	- 55' AN	D 60' SPANS			
MARK	SIZE	NO.	FORM	LENGTH	LENGTH VARIATION			
	EPOXY COATED REINFORCING							
P1	#4	20	BNT.	6'-3"				
P2	#4	16	BNT.	7'-3"				
PH	#4	4	BNT.	13'-5"				
	1.1		10	12	Ž.			
VDI I	TARENT	r DAI	DILICT	CE! THE	ILL OO! CDANC			


ABU	TMENT	BAI	RLIST	- 65' THE	RU 80' SPANS			
MARK	SIZE	NO.	FORM	LENGTH	LENGTH VARIATION			
	EPOXY COATED REINFORCING							
P1	#4	20	BNT.	6'-3"				
P2	#4	16	BNT.	7'-3"				
PH	#4	2	BNT.	13'-5"				

ABUT	MENT	BAR	LIST	- 85'	THRU	100'	SPANS
MARK	SIZE	NO.	FORM	LENG	STH	LENGTH	VARIATION
		EPC	XY COA	TED REI	NFORCI	NG	
P3	#4	20	BNT.	5'-8	8"		
P4	#4	16	BNT.	6'-8	8"		



WATER REPELLENT TREATMENT DETAILS

WING ELEVATION



WPI #4 x 8'-8"

ABUTMENT QUANTITIES	3	
ITEM	UNIT	TOTAL
SUBSTRUCTURE EXCAVATION COMMON	C.Y.	80
CLSM BACKFILL	C.Y.	85
CLASS A CONCRETE	C.Y.	39.3
EPOXY COATED REINFORCING STEEL	LB.	5,190
PILES, FURNISHED (HP10x42)	L.F.	
PILES, FURNISHED (HP12x53)	L.F.	
PILES, DRIVEN (HP10x42)	L.F.	
PILES, DRIVEN (HP12x53)	L.F.	
WATER REPELLENT (VISUALLY INSPECTED)	S.Y.	42
6" PERFORATED PIPE UNDERDRAIN ROUND	L.F.	42
6" NON-PERF. PIPE UNDERDRAIN RND.	L.F.	

0 00.001	DATE	110110
		OF TRANSPORTATION NDARD (ENGLISH)

ABUTMENT DETAILS
55' THRU 100' ROLLED BEAM SPANS

CONVENTIONAL (SHEET 2 OF 2)

2009 SPECIFICATIONS B40-C-ABUT-RB-55100-2

B-251E

① 2 Sets of 21 ② 2 Sets of 3③ 4 Sets of 6

(4) 4 Sets of 14