

**OKLAHOMA DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISION
FOR
SAND CUSHION**

This Special Provision revises, amends and where in conflict, supersedes applicable sections of the Standard Specifications for Highway Construction, Edition of 1988, and thereto the Supplement, Edition of 1991, the 1996 Standard Specifications for Highway Construction, Metric, or the 1999 Standard Specifications for Highway Construction, English and Metric, as applicable. Units of measurement are provided in the subsections in both English and Metric equivalents. The units applicable for this project will be those specified in the project plans.

(add the following:)

308.01. DESCRIPTION.

This work shall consist of furnishing and placing a course of sandy material as a foundation for concrete pavement in accordance with these Specifications and in reasonably close conformity with the lines, grades and typical cross sections shown on the Plans or established by the Engineer.

308.02. MATERIALS.

Materials shall meet the requirements specified in Subsection 704.02.

308.04. CONSTRUCTION METHODS.

(a) Preparation of Subgrade. Construct the subgrade as specified for method B of Section 310 of these Specifications or the method indicated on the Plans and in the Proposal.

(b) Compaction-Density. Place the sand cushion material on the roadbed in sufficient quantities and uniformly spread to such a thickness and width that the completed sand cushion will conform to the Plan width, thickness and grade within the specified tolerances.

Manipulate, sprinkle and roll the sand cushion material to secure not less than 100 percent of standard density.

(c) Tolerances. Tolerances for surface, width and thickness shall be in conformity with Section 301.

308.05. METHOD OF MEASUREMENT.

Sand cushion will be measured by the cubic yard (cubic meter) as shown on the Plans and in the Proposal.

308.06. BASIS OF PAYMENT.

Accepted quantities of sand cushion, measured as provided above, will be paid for at the contract unit price for:

SAND CUSHION.....CUBIC YARD (CUBIC METER)

which shall be full compensation for furnishing all materials, equipment, labor and incidentals to complete the work as specified.