

**OKLAHOMA DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISIONS
FOR
PORTLAND CEMENT CONCRETE PAVEMENT**

These Special Provisions revise, amend, and where in conflict, supersede applicable sections of the Standard Specifications for Highway Construction, English, Edition of 1988, and the Supplement thereto, Edition of 1991, the Standard Specifications for Highway Construction, Edition of 1996, or the Standard Specifications for Highway Construction, Edition of 1999 as applicable. Units of measurement are provided in the subsections in both English and Metric equivalents. The units applicable for this project will be those specified in the project plans.

414.04. CONSTRUCTION METHODS. *(revise as follows)*

- (q) Opening to Traffic.** Exclude traffic from the newly constructed pavement for a period of 14 days after the concrete is placed or longer if weather conditions make it advisable to extend this time. However, at the discretion of the Engineer, the pavement may be opened to traffic when the strength specified in Subsection 701.01 is obtained.
- (r) High-Early-Strength Concrete Pavement.**
- (1) General Requirements.** When high-early-strength concrete pavement is specified, it shall meet the requirements of Section 701.
 - (2) Opening to Traffic.** Exclude traffic from the newly constructed pavement until the strength specified in Subsection 701.01 is obtained.
 - (3) Joints.** Construct all joints in accordance with Subsection 414.04(j).