



● MINIMUM DEPTH MASONRY
OR PRECAST WALLS
2'- 3" FOR 18" RCP
2'- 9" FOR 24" RCP
3'- 3" FOR 30" RCP
3'- 9" FOR 36" RCP

DECION	TYPE	DIMENSIONS	
NO.	OF CURB	а	b
1	4" MOUNTABLE	4½"	9½"
	6" MOUNTABLE	6½"	11½"
	6" BARRIER	6½"	11½"
	8" BARRIER	8½"	13½"
2	4" MOUNTABLE	4½"	9½"
	6" MOUNTABLE	6½"	11½"
	6" BARRIER	6½"	11½"
	8" BARRIER	8½"	13½"
3	4" MOUNTABLE	4½"	9½"
	6" MOUNTABLE	6½"	11½"
	6" BARRIER	6½"	111/2"
	8" BARRIER	8½"	13½"

ADDITIONAL OPENINGS



DETAIL OF CONNECTION ANGLE IRON & CAST IRON HOOD NOTE: ANGLE IRON TO BE BOLTED TO HOOD WITH 3 EACH - 3/4 " x 12" MACHINE BOLTS IN EACH HOOD SECTION.

BASIS OF PAYMENT				
ITEM NO.	ITEM			
611(G)	INLET ( CI DES. ▲ )	ΕA		
611 (H)	ADDITIONAL DEPTH IN INLET ( CI DES. $oldsymbol{ abla}$ )	VF		
611(1)	REPLACEMENT OF INLET FRAME AND GRATE▲	ΕA		
611 (J)	REPLACEMENT OF INLET FRAME	ΕA		
611(K)	REPLACEMENT OF INLET GRATE	ΕA		
611 (M)	REPLACEMENT OF CAST IRON HOOD	ΕA		

▲ SPECIFY INLET DESIGN & CURB OPENING DESIGNATION.

▼ SPECIFY INLET DESIGN 1, 2 OR 3.

▲ TYPE OF FRAME AND TYPE OF GRATE SHALL BE SPECIFIED.



\_DATE: 4/1/2025

ROADWAY DESIGN DIVISION STANDARD

CAST-IN-PLACE CURB INLETS



2019 SPECIFICATIONS

CI-2