DESCRIPTION REVISIONS

FLUORESCENT ORANGE & NOTES 6/27/08




ROAD WORK SIGN

48 x 48 16.00 SF CW20-1 COLOR:

LEGEND AND BORDER:

BLACK (NON-REFLECTORIZED) **BACKGROUND:** 

FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED)



DETOUR SIGN

48 x 48 16.00 SF CW20-2 COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) **BACKGROUND:** 



DETOUR AHEAD SIGN

CW20-2A 48 x 48 16.00 SF COLOR:

LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) BACKGROUND:



ROAD CLOSED SIGN

CW20-3  $48 \times 48$  16.00 SF COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) **BACKGROUND:** 

| FLUORESCENT ORANGE (REFLECTORIZED) | FLUORESCENT ORANGE (REFLECTORIZED)



STREET CLOSED SIGN

CW20-3A  $48 \times 48$  16.00 SF

COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) BACKGROUND:



ONE LANE ROAD SIGN

CW20-4 48 × 48 16.00 SF

COLOR:

LEGEND AND BORDER:

BLACK (NON-REFLECTORIZED) **BACKGROUND:** 



LEFT LANE CLOSED SIGN

CW20-5(L)  $48 \times 48$  16.00 SF COLOR:

LEGEND AND BORDER: BACKGROUND:

BLACK (NON-REFLECTORIZED)



RIGHT LANE CLOSED SIGN

CW20-5(R) 48 × 48 16.00 SF COLOR:

LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) **BACKGROUND:** 



FLAGGER SIGN

CW20-7 48 x 48 16.00 SF

COLOR: LEGEND AND BORDER:

BLACK (NON-REFLECTORIZED) **BACKGROUND:** 



FLAGGER SIGN

CW20-7A 48 x 48 16.00 SF

COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED)

**BACKGROUND:** FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED)



**WORKERS SIGN** 

 $48 \times 48 \quad 16.00 \text{ SF}$ CW21-1

COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED)

BACKGROUND: FLUORESCENT ORANGE (REFLECTORIZED) FLUORESCENT ORANGE (REFLECTORIZED)



WORKERS SIGN

CW21-1a  $48 \times 48$  16.00 SF

COLOR: LEGEND AND BORDER: BLACK (NON-REFLECTORIZED) BACKGROUND:

NOTES:

WORD SIGNS MAY BE USED IF SYMBOL SIGNS ARE NOT AVAILABLE EITHER IN "STANDARD HIGHWAY SIGNS MANUAL" OR IN THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" (MUTCD) (CURRENT EDITION).

ALL DIAMOND SHAPE CONSTRUCTION WARNING SIGNS SHALL BE 48 INCHES X 48 INCHES UNLESS OTHERWISE NOTED IN THE PLANS.

\* SUPPLEMENTAL SIGNS SHALL ONLY BE USED IN CONJUCTION WITH DIAMOND SHAPE CONSTRUCTION WARNING SIGNS. THE SIZE OF SUPPLEMENTAL SIGNS SHALL BE APPROPRIATE FOR USE WITH A 48 INCH x 48 INCH WARNING SIGN UNLESS OTHERWISE NOTED IN THE PLANS.

	BASIS OF PAYMENT	
ITEM NO.	ITEM	UNIT
880.06(B)	CONSTRUCTION SIGNS	SD

APPROVED BY TRAFFIC ENGINEER Guld Smark

DATE 6/3408

OKLAHOMA DEPT. OF TRANSPORTATION TRAFFIC STANDARD (ENGLISH) TRAFFIC CONTROL STANDARD CONSTRUCTION SIGNS

1999 SPECIFICATIONS

TCS9-1C

T-509CE